

Pari-GP reference card

(PARI-GP version 2.17.2)

Note: optional arguments are surrounded by braces {}.

To start the calculator, type its name in the terminal: **gp**

To exit **gp**, type **quit**, **\q**, or **<C-D>** at prompt.

Help

describe function	?function
extended description	??keyword
list of relevant help topics	???pattern
name of GP-1.39 function f in GP-2.*	whatnow(f)

Input/Output

previous result, the result before	%, %`, %`` , etc.
n -th result since startup	% n
separate multiple statements on line	;
extend statement on additional lines	\
extend statements on several lines	{ seq_1 ; seq_2 ;}
comment	/* ... */
one-line comment, rest of line ignored	\\ ...

Metacommands & Defaults

set default d to val	default({ d },{ val })
toggle timer on/off	#
print time for last result	##
print defaults	\d
set debug level to n	\g n
set memory debug level to n	\gm n
set n significant digits / bits	\p n , \pb n
set n terms in series	\ps n
quit GP	\q
print the list of PARI types	\t
print the list of user-defined functions	\u
read file into GP	\r $filename$
set debuglevel for domain D to n	setdebug(D,n)

Debugger / break loop

get out of break loop	break or <C-D>
go up/down n frames	dbg_up({ n }), dbg_down
set break point	breakpoint()
examine object o	dbg_x(o)
current error data	dbg_err()
number of objects on heap and their size	getheap()
total size of objects on PARI stack	getstack()

PARI Types & Input Formats

t_INT . Integers; hex, binary	± 31 ; $\pm 0x1F$, $\pm 0b101$
t_REAL . Reals	± 3.14 , 6.022 E23
t_INTMOD . Integers modulo m	Mod(n,m)
t_FRAC . Rational Numbers	n/m
t_FFELT . Elt in finite field \mathbf{F}_q	ffgen(q , 't)
t_COMPLEX . Complex Numbers	$x + y * I$
t_PADIC . p -adic Numbers	$x + O(p^k)$
t_QUAD . Quadratic Numbers	$x + y * \text{quadgen}(D, \{ 'w \})$
t_POLMOD . Polynomials modulo g	Mod(f,g)
t_POL . Polynomials	$a * x^n + \dots + b$
t_SER . Power Series	$f + O(x^k)$
t_RFRAC . Rational Functions	f/g
t_QFB . Binary quadratic form	Qfb(a,b,c)
t_VEC/t_COL . Row/Column Vectors	[x,y,z], [x,y,z]~
t_VEC integer range	[1..10]

t_VECSMALL . Vector of small ints	Vecsmall([x,y,z])
t_MAT . Matrices	[$a,b;c,d$]
t_LIST . Lists	List([x,y,z])
t_STR . Strings	"abc"
t_INFINITY . $\pm\infty$	+oo, -oo

Reserved Variable Names

$\pi \approx 3.14$, $\gamma \approx 0.57$, $C \approx 0.91$, $I = \sqrt{-1}$	Pi, Euler, Catalan, I
Landau's big-oh notation	O

Information about an Object, Precision

PARI type of object x	type(x)
length of x / size of x in memory	# x , sizebyte(x)
real precision / bit precision of x	precision(x), bitprecision(x)
p -adic, series prec. of x	padicprec(x,p), serprec(x,v)
current dynamic precision	getlocalprec, getlocalbitprec

Operators

basic operations	+, -, *, /, ^, sqr
$i \leftarrow i+1$, $i \leftarrow i-1$, $i \leftarrow i*j$, ...	i++, i--, i*=j,...
Euclidean quotient, remainder	$x \backslash y$, $x \backslash y$, $x \% y$, divrem(x,y)
shift x left or right n bits	$x << n$, $x >> n$ or shift($x, \pm n$)
multiply by 2^n	shiftmul(x,n)
comparison operators	<=, <, >=, >, ==, !=, ==, lex, cmp
boolean operators (or, and, not)	, &&, !
bit operations	bitand, bitneg, bitor, bitxor, bitnegimply
maximum/minimum of x and y	max(x,y), min(x,y)
sign of x (gives $-1, 0, 1$)	sign(x)
binary exponent of x	exponent(x)
derivative of f , 2nd derivative, etc.	f' , f'' , ...
differential operator	diffop($f,v,d,\{n=1\}$)
quote operator (formal variable)	'x
assignment	x = value
simultaneous assignment $x \leftarrow v[1]$, $y \leftarrow v[2]$	[x,y] = v

Select Components

<i>Caveat</i> : components start at index $n = 1$.	
n -th component of x	component(x,n)
n -th component of vector/list x	$x[n]$
components $a, a+1, \dots, b$ of vector x	$x[a..b]$
(m,n) -th component of matrix x	$x[m,n]$
row m or column n of matrix x	$x[m,]$, $x[,n]$
numerator/denominator of x	numerator(x), denominator(x)

Random Numbers

random integer/prime in $[0,N[$	random(N), randomprime(N)
get/set random seed	getrand, setrand(s)

Conversions

to vector, matrix, vec. of small ints	Col/Vec, Mat, Vecsmall
to list, set, map, string	List, Set, Map, Str
create $(x \bmod y)$	Mod(x,y)
make x a polynomial of v	Pol($x,\{v\}$)
variants of Pol <i>et al.</i> , in reverse order	Polrev, Vecrev, Colrev
make x a power series of v	Ser($x,\{v\}$)
convert x to simplest possible type	simplify(x)
object x with real precision n	precision(x,n)
object x with bit precision n	bitprecision(x,n)
set precision to p digits in dynamic scope	localprec(p)
set precision to p bits in dynamic scope	localbitprec(p)

Character strings

convert to TeX representation	strtex(x)
string from bytes / from format+args	strchr, sprintf
split string / join strings	strsplit, strjoin
convert time t ms. to h, m, s, ms format	strtime(t)
Conjugates and Lifts	
conjugate of a number x	conj(x)
norm of x , product with conjugate	norm(x)
L^p norm of x (L^∞ if no p)	normlp($x,\{p\}$)
square of L^2 norm of x	norml2(x)
lift of x from Mods and p -adics	lift, centerlift(x)
recursive lift	liftall
lift all t_INT and t_PADIC (\rightarrow t_INT)	liftint
lift all t_POLMOD (\rightarrow t_POL)	liftpol

Lists, Sets & Maps

Sets (= row vector with strictly increasing entries w.r.t. cmp)	
intersection of sets x and y	setintersect(x,y)
set of elements in x not belonging to y	setminus(x,y)
symmetric difference $x \Delta y$	setdelta(x,y)
union of sets x and y	setunion(x,y)
does y belong to the set x	setsearch($x,y,\{flag\}$)
set of all $f(x,y)$, $x \in X$, $y \in Y$	setbinop(f,X,Y)
is x a set ?	setisset(x)

Lists . create empty list: $L = \text{List}()$	
append x to list L	listput($L,x,\{i\}$)
remove i -th component from list L	listpop($L,\{i\}$)
insert x in list L at position i	listinsert(L,x,i)
sort the list L in place	listsort($L,\{flag\}$)
Maps . create empty dictionary: $M = \text{Map}()$	
attach value v to key k	mapput(M,k,v)
recover value attach to key k or error	mapget(M,k)
is key k in the dict? (set v to $M(k)$)	mapisdefined($M,k,\{\&v\}$)
evaluate f at $M(k)$	mapapply(M,k,f)
remove k from map domain	mapdelete(M,k)

GP Programming

User functions and closures

x,y are formal parameters; y defaults to Pi if parameter omitted;
 z,t are local variables (lexical scope), z initialized to 1.

fun (x , y =Pi) = my(z =1, t); seq	
fun = (x , y =Pi) -> my(z =1, t); seq	
attach help message h to s	addhelp(s,h)
undefine symbol s (also kills help)	kill(s)
Control Statements (X : formal parameter in expression seq)	
if $a \neq 0$, evaluate seq_1 , else seq_2	if($a,\{seq_1\},\{seq_2\}$)
eval. seq for $a \leq X \leq b$	for($X = a,b,seq$)
...for $X \in v$	foreach(v,X,seq)
...for primes $a \leq X \leq b$	forprime($X = a,b,seq$)
...for primes $\equiv a \pmod{q}$	forprimestep($X = a,b,q,seq$)
...for composites $a \leq X \leq b$	forcomposite($X = a,b,seq$)
...for $a \leq X \leq b$ stepping s	forstep($X = a,b,s,seq$)
...for X dividing n	fordiv(n,X,seq)
... $X = [n, factor(n)]$, $a \leq n \leq b$	forfactored($X = a,b,seq$)
...as above, n squarefree	forsquarefree($X = a,b,seq$)
... $X = [d, factor(d)]$, $d \mid n$	fordivfactored(n,X,seq)
multivariable for , lex ordering	forvec($X = v,seq$)

loop over partitions of n
... permutations of S
... subsets of $\{1, \dots, n\}$
... k -subsets of $\{1, \dots, n\}$
... vectors $v, q(v) \leq B; q > 0$
... $H < G$ finite abelian group
evaluate seq until $a \neq 0$
while $a \neq 0$, evaluate seq
exit n innermost enclosing loops
start new iteration of n -th enclosing loop
return x from current subroutine

Exceptions, warnings
raise an exception / warning
type of error message E
try seq_1 , evaluate seq_2 on error

Functions with closure arguments / results
number of arguments of f
select from v according to f
apply f to all entries in v
evaluate $f(a_1, \dots, a_n)$
evaluate $f(\dots f(f(a_1, a_2), a_3) \dots, a_n)$
calling function as closure

Sums & Products
sum $X = a$ to $X = b$, initialized at x
sum entries of vector v
product of all vector entries
sum $expr$ over divisors of n
... assuming $expr$ multiplicative
product $a \leq X \leq b$, initialized at x
product over primes $a \leq X \leq b$

Sorting
sort x by k -th component
min. m of x ($m = x[i]$), max.
does y belong to x , sorted wrt. f
 $\prod g^x \rightarrow$ factorization (\Rightarrow sorted, unique g)

Input/Output
print with/without $\backslash n$, TeX format
pretty print matrix
print fields with separator
formatted printing
write $args$ to file
write x in binary format
read file into GP
... return as vector of lines
... return as vector of strings
read a string from keyboard

Files and file descriptors
File descriptors allow efficient small consecutive reads or writes from or to a given file. The argument n below is always a descriptor, attached to a file in **r**(ead), **w**(rite) or **a**(ppend) mode.
get descriptor n for file $path$ in given $mode$
... from shell cmd output (pipe)

close descriptor
commit pending write operations
read logical line from file
... raw line from file
write $s \backslash n$ to file
... write s to file

forpart($p = n, seq$)
forperm(S, p, seq)
forsubset(n, p, seq)
forsubset($[n, k], p, seq$)
forqfvec(v, q, b, seq)
forsubgroup($H = G$)
until(a, seq)
while(a, seq)
break($\{n\}$)
next($\{n\}$)
return($\{x\}$)

error(), warning()
errname(E)
iferr(seq_1, E, seq_2)

arity(f)
select(f, v)
apply(f, v)
call(f, a)
fold(f, a)
self()

sum($X = a, b, expr, \{x\}$)
vecsum(v)
vecprod(v)
sumdiv($n, X, expr$)
sumdivmult($n, X, expr$)
prod($X = a, b, expr, \{x\}$)
prodeuler($X = a, b, expr$)

vecsort($x, \{k\}, \{fl = 0\}$)
vecmin($x, \{\&i\}$), vecmax
vecsearch($x, y, \{f\}$)
matreduce(m)

print, print1, printtex
printp
printsep(sep, \dots), printsep1
printf()

write, write1, writetex($file, args$)
writebin($file, x$)
read($\{file\}$)
readvec($\{file\}$)
readstr($\{file\}$)
input()

Pari-GP reference card

(PARI-GP version 2.17.2)

Timers
CPU time in ms and reset timer
CPU time in ms since gp startup
time in ms since UNIX Epoch
timeout command after s seconds

Interface with system
allocates a new stack of s bytes
alias old to new
install function from library
execute system command a
... and feed result to GP
... returning GP string
get \$VAR from environment
expand env. variable in string

gettime()
getabstime()
getwalltime()
alarm($s, expr$)

allocatemem($\{s\}$)
alias(new, old)
install($f, code, \{gpf\}, \{lib\}$)
system(a)
extern(a)
externstr(a)
getenv("VAR")
strexpend(x)

Parallel evaluation

These functions evaluate their arguments in parallel (pthreads or MPI); args. must not access global variables (use export for this) and must be free of side effects. Enabled if threading engine is not *single* in gp header.

evaluate f on $x[1], \dots, x[n]$
evaluate closures $f[1], \dots, f[n]$
as select
as sum
as vector
eval f for $i = a, \dots, b$
... for each element x in v
... for p prime in $[a, b]$
... for $p = a \bmod q$
... for $i = a, a + s, \dots, b$
... multivariate
export x to parallel world
... all dynamic variables
frees exported value x
... all exported values

parapply(f, x)
pareval(f)
parselect($f, A, \{flag\}$)
parsum($i = a, b, expr$)
parvector($n, i, \{expr\}$)
parfor($i = a, \{b\}, f, \{r\}, \{f_2\}$)
parforeach($v, x, f, \{r\}, \{f_2\}$)
parforprime($p = a, \{b\}, f, \{r\}, \{f_2\}$)
parforprimestep($p = a, \{b\}, q, f, \{r\}, \{f_2\}$)
parforstep($i = a, \{b\}, s, f, \{r\}, \{f_2\}$)
parforvec($X = v, f, \{r\}, \{f_2\}, \{flag\}$)

export(x)
exportall()
unexport(x)
unexportall()

Linear Algebra

dimensions of matrix x
multiply two matrices
... assuming result is diagonal
concatenation of x and y
extract components of x
transpose of vector or matrix x
adjoint of the matrix x
eigenvectors/values of matrix x
characteristic/minimal polynomial of x
trace/determinant of matrix x
permanent of matrix x
Frobenius form of x
QR decomposition
apply matqr's transform to v

matsize(x)
 $x * y$
matmultodiagonal(x, y)
concat($x, \{y\}$)
vecextract($x, y, \{z\}$)
 $x \sim$, mattranspose(x)
matadjoin(x)
mateigen(x)
charpoly(x), minpoly(x)
trace(x), matdet(x)
matpermanent(x)
matfrobenius(x)
matqr(x)
mathouseholder(Q, v)

Constructors & Special Matrices

$\{g(x) : x \in v \text{ s.t. } f(x)\}$
 $\{x : x \in v \text{ s.t. } f(x)\}$
 $\{g(x) : x \in v\}$
row vec. of $expr$ eval'd at $1 \leq i \leq n$
col. vec. of $expr$ eval'd at $1 \leq i \leq n$
vector of small ints

[g(x) | x <- v, f(x)]
[x | x <- v, f(x)]
[g(x) | x <- v]
vector($n, \{i\}, \{expr\}$)
vectorv($n, \{i\}, \{expr\}$)
vectorsmall($n, \{i\}, \{expr\}$)

$[c, c \cdot x, \dots, c \cdot x^n]$
 $[1, 2^x, \dots, n^x]$
matrix $1 \leq i \leq m, 1 \leq j \leq n$
define matrix by blocks
diagonal matrix with diagonal x
is x diagonal?
 $x \cdot \text{matdiagonal}(d)$
 $n \times n$ identity matrix
Hessenberg form of square matrix x
 $n \times n$ Hilbert matrix $H_{ij} = (i + j - 1)^{-1}$
 $n \times n$ Pascal triangle
companion matrix to polynomial x
Sylvester matrix of x and y

powers($x, n, \{c = 1\}$)
dirpowers(n, x)
matrix($m, n, \{i\}, \{j\}, \{expr\}$)
matconcat(B)
matdiagonal(x)
matisdiagonal(x)
matmuldiagonal(x, d)
matid(n)
mathess(x)
mathilbert(n)
matpascal($n - 1$)
matcompanion(x)
polsylvestermatrix(x, y)

Gaussian elimination

kernel of matrix x
intersection of column spaces of x and y
solve $MX = B$ (M invertible)
one sol of $M * X = B$
basis for image of matrix x
columns of x *not* in **matimage**
supplement columns of x to get basis
rows, cols to extract invertible matrix
rank of the matrix x
solve $MX = B \bmod D$
image mod D
kernel mod D
inverse mod D
determinant mod D

matker($x, \{flag\}$)
matintersect(x, y)
matsolve(M, B)
matinverseimage(M, B)
matimage(x)
matimagecompl(x)
matsupplement(x)
matindexrank(x)
matrank(x)
matsolvemod(M, D, B)
matimagemod(M, D)
matkermod(M, D)
matinvmod(M, D)
matdetmod(M, D)

Lattices & Quadratic Forms

Quadratic forms

evaluate ${}^t x Q y$
evaluate ${}^t x Q x$
signature of quad form ${}^t y * x * y$
decomp into squares of ${}^t y * x * y$
eigenvalues/vectors for real symmetric x
Cholesky decomposition of x

qfeval($\{Q = id\}, x, y$)
qfeval($\{Q = id\}, x$)
qfsign(x)
qfgaussred(x)
qfjacobi(x)
qfcholesky(x)

HNF and SNF

upper triangular Hermite Normal Form
HNF of x where d is a multiple of $\det(x)$
multiple of $\det(x)$
HNF of $(x \mid \text{diagonal}(D))$
elementary divisors of x
 q -rank from elementary divisors
elementary divisors of $\mathbf{Z}[a]/(f'(a))$
integer kernel of x
Z-module \leftrightarrow **Q**-vector space

mathnf(x)
mathnfmod(x, d)
matdetint(x)
mathnfmodid(x, D)
matsnf(x)
snfrank(v, q)
poldiscduced(f)
matkerint(x)
matrixqz(x, p)

Lattices

LLL-algorithm applied to columns of x
... for Gram matrix of lattice
find up to m sols of $qfeval(x, y) \leq b$
... up to m closest vectors to t
 $v, v[i] :=$ number of y s.t. $qfeval(x, y) = i$
perfection rank of x
find isomorphism between q and Q

qflll($x, \{flag\}$)
qflllgram($x, \{flag\}$)
qfminim(x, b, m)
qfcvp(x, t, m)
qfrep($x, B, \{flag\}$)
qfperfection(x)
qfisom(q, Q)

precompute for isomorphism test with q	qfisominit(q)
automorphism group of q	qfauto(q)
convert qfauto for GAP/Magma	qfautoexport($G, \{flag\}$)
orbits of V under $G \subset \text{GL}(V)$	qforbits(G, V)
Polynomials & Rational Functions	
all defined polynomial variables	variables()
get var. of highest priority (higher than v)	varhigher($name, \{v\}$)
... of lowest priority (lower than v)	varlower($name, \{v\}$)
Coefficients, variables and basic operators	
degree of f	poldegree(f)
coef. of degree n of f , leading coef.	polcoef(f, n), pollead
main variable / all variables in f	variable(f), variables(f)
replace x by y in f	subst(f, x, y)
evaluate f replacing vars by their value	eval(f)
replace polynomial expr. $T(x)$ by y in f	substpol(f, T, y)
replace x_1, \dots, x_n by y_1, \dots, y_n in f	substvec(f, x, y)
$f \in A[x]$; reciprocal polynomial $x^{\deg f} f\left(\frac{1}{x}\right)$	polrecip(f)
gcd of coefficients of f	content(f)
derivative of f w.r.t. x	deriv($f, \{x\}$)
... n -th derivative of f	derivn($f, n, \{x\}$)
formal integral of f w.r.t. x	intformal($f, \{x\}$)
formal sum of f w.r.t. x	sumformal($f, \{x\}$)
Constructors & Special Polynomials	
interpolation polynomial at $(x[1], y[1]), \dots, (x[n], y[n])$, evaluated at t , with error estimate e	polinterpolate($x, \{y\}, \{t\}, \{&e\}$)
monic polynomial from roots r	polfromroots(r)
$T_n/U_n, H_n$	polchebyshev(n), polhermite(n)
$P_n, L_n^{(\alpha)}$	pollegendre(n), pollaguerre(n, a)
n -th cyclotomic polynomial Φ_n	polcyclo(n)
return n if $f = \Phi_n$, else 0	poliscyclo(f)
is f a product of cyclotomic polynomials?	poliscycloprod(f)
Zagier's polynomial of index (n, m)	polzagier(n, m)
Resultant, elimination	
discriminant of polynomial f	poldisc(f)
find factors of poldisc(f)	poldiscfactors(f)
resultant $R = \text{Res}_v(f, g)$	polresultant($f, g, \{v\}$)
$[u, v, R], xu + yv = \text{Res}_v(f, g)$	polresultantext($x, y, \{v\}$)
solve Thue equation $f(x, y) = a$	thue($t, a, \{sol\}$)
initialize t for Thue equation solver	thueinit(f)
Roots and Factorization (Complex/Real)	
complex roots of f	polroots(f)
bound complex roots of f	polrootsbound(f)
number of real roots of f (in $[a, b]$)	polsturm($f, \{[a, b]\}$)
real roots of f (in $[a, b]$)	polrootsreal($f, \{[a, b]\}$)
complex embeddings of $t.\text{POLMOD } z$	conjvec(z)
Roots and Factorization (Finite fields)	
factor $f \bmod p$, roots	factormod(f, p), polrootsmod
factor f over $\mathbf{F}_p[x]/(T)$, roots	factormod($f, [T, p]$), polrootsmod
squarefree factorization of f in $\mathbf{F}_q[x]$	factormodSQF($f, \{D\}$)
distinct degree factorization of f in $\mathbf{F}_q[x]$	factormodDDF($f, \{D\}$)
factor n -th cyclotomic pol. $\Phi_n \bmod p$	factormodcyclo(n, p)
Roots and Factorization (p-adic fields)	
factor f over \mathbf{Q}_p , roots	factorpadic(f, p, r), polrootspadic
p -adic root of f congruent to $a \bmod p$	padicappr(f, a)
Newton polygon of f for prime p	newtonpoly(f, p)
Hensel lift $A/\text{lcl}(A) = \prod_i B[i] \bmod p^e$	polhensellift(A, B, p, e)

Pari-GP reference card	
(PARI-GP version 2.17.2)	
$T = \prod (x - z_i) \mapsto \prod (x - \omega(z_i)) \in \mathbf{Z}_p[x]$	polteichmuller(T, p, e)
extensions of \mathbf{Q}_p of degree N	padicfields(p, N)
Roots and Factorization (Miscellaneous)	
symmetric powers of roots of f up to n	polsym(f, n)
Graeffe transform of $f, g(x^2) = f(x)f(-x)$	polgraeffe(f)
factor f over coefficient field	factor(f)
cyclotomic factors of $f \in \mathbf{Q}[X]$	polcyclofactors(f)
Finite Fields	
A finite field is encoded by any element ($t.\text{FFELT}$).	
find irreducible $T \in \mathbf{F}_p[x]$, $\deg T = n$	ffinit($p, n, \{x\}$)
Create t in $\mathbf{F}_q \simeq \mathbf{F}_p[t]/(T)$	$t = \text{ffgen}(T, 't)$
... indirectly, with implicit T	$t = \text{ffgen}(q, 't'); T = t.\text{mod}$
map m from $\mathbf{F}_q \ni a$ to $\mathbf{F}_{q^k} \ni b$	$m = \text{ffembed}(a, b)$
build $K = \mathbf{F}_q[x]/(P)$ extending $\mathbf{F}_q \ni a$,	ffextend(a, P)
evaluate map m on x	ffmap(m, x)
inverse map of m	ffinvmap(m)
compose maps $m \circ n$	ffcompomap(m, n)
x as polmod over codomain of map m	ffmaprel(m, x)
F^n over $\mathbf{F}_q \ni a$	fffrobenius(a, n)
$\#\{\text{monic irred. } T \in \mathbf{F}_q[x], \deg T = n\}$	ffnbirred(q, n)
Formal & p-adic Series	
truncate power series or p -adic number	truncate(x)
valuation of x at p	valuation(x, p)
Dirichlet and Power Series	
Taylor expansion around 0 of f w.r.t. x	taylor(f, x)
Laurent series of closure F up to x^k	laurentseries(f, k)
$\sum a_k b_k t^k$ from $\sum a_k t^k$ and $\sum b_k t^k$	serconvol(a, b)
$f = \sum a_k t^k$ from $\sum (a_k/k!) t^k$	serlaplace(f)
reverse power series F so $F(f(x)) = x$	serreverse(f)
remove terms of degree $< n$ in f	serchop(f, n)
Dirichlet series multiplication / division	dirmul, dirdiv(x, y)
Dirichlet Euler product (b terms)	direuler($p = a, b, expr$)
Transcendental and p-adic Functions	
real, imaginary part of x	real(x), imag(x)
absolute value, argument of x	abs(x), arg(x)
square/ n th root of x	sqrt(x), sqrtsn($x, n, \{&z\}$)
all n -th roots of 1	rootsof1(n)
FFT of $[f_0, \dots, f_{n-1}]$	$w = \text{fftinit}(n), \text{fft}/\text{fftin}(w, f)$
trig functions	sin, cos, tan, cotan, sinc
inverse trig functions	asin, acos, atan
hyperbolic functions	sinh, cosh, tanh, cotanh
inverse hyperbolic functions	asinh, acosh, atanh
$\log(x), \log(1+x), e^x, e^x - 1$	log, loglp, exp, expm1
Euler Γ function, $\log \Gamma, \Gamma'/\Gamma$	gamma, lngamma, psi
half-integer gamma function $\Gamma(n+1/2)$	gammah(n)
Riemann's zeta $\zeta(s) = \sum n^{-s}$	zeta(s)
$\sum_{1 \leq n \leq N} n^s$	dirpowerssum(N, s)
Hurwitz's $\zeta(s, x) = \sum (n+x)^{-s}$	zetahurwitz(s, x)
Lerch $\Phi(z, s, x) = \sum z^n (n+x)^{-s}$	lerchphi(z, s, x)
Lerch $L(s, x, t) = \Phi(e^{2i\pi t}, s, x)$	lerchzeta(s, x, t)
multiple zeta value (MZV), $\zeta(s_1, \dots, s_k)$	zetamult($s, \{T\}$)
all MZVs for weight $\sum s_i = n$	zetamultall(n)
convert MZV id to $[s_1, \dots, s_k]$	zetamultconvert($f, \{flag\}$)
MZV dual sequence	zetamultdual(s)
multiple polylog $Li_{s_1, \dots, s_k}(z_1, \dots, z_k)$	polylogmult(s, z)

incomplete Γ function ($y = \Gamma(s)$)	incgam($s, x, \{y\}$)
complementary incomplete Γ	incgamc(s, x)
$\int_x^\infty e^{-t} dt/t, (2/\sqrt{\pi}) \int_x^\infty e^{-t^2} dt$	eint1, erfc
elliptic integral of 1st and 2nd kind	ellK(k), ellE(k)
dilogarithm of x	dilog(x)
m -th polylogarithm of x	polylog($m, x, \{flag\}$)
U -confluent hypergeometric function	hyperu(a, b, u)
Hypergeometric ${}_pF_q(A, B; z)$	hypergeom(A, B, z)
Bessel $J_n(x), J_{n+1/2}(x)$	besselj(n, x), besseljh(n, x)
Bessel $I_\nu, K_\nu, H_\nu^1, H_\nu^2, Y_\nu$	(bessel)i, k, h1, h2, y
k -th zero of $J_\nu(x)$	besseljzero($nu, \{k=1\}$)
k -th zero of $Y_\nu(x)$	besselyzero($nu, \{k=1\}$)
Airy functions $A_i(x), B_i(x)$	airy(x)
Lambert $W: x$ s.t. $xe^x = y$	lambertw(y)
Teichmuller character of p -adic x	teichmuller(x)
Iterations, Sums & Products	
Numerical integration for meromorphic functions	
Behaviour at endpoint for Double Exponential (DE) methods: either a scalar ($a \in \mathbf{C}$, regular) or $\pm\infty$ (decreasing at least as x^{-2}) or	
$(x-a)^{-\alpha}$ singularity	$[a, a]$
exponential decrease $e^{-\alpha x }$	$[\pm\infty, a], \alpha > 0$
slow decrease $ x ^\alpha$	$\dots \alpha < -1$
oscillating as $\cos(kx)$	$\alpha = k\mathbf{I}, k > 0$
oscillating as $\sin(kx)$	$\alpha = -k\mathbf{I}, k > 0$
numerical integration	intnum($x = a, b, f, \{T\}$)
weights T for intnum	intnuminit($a, b, \{m\}$)
weights T incl. kernel K	intfuncinit($t = a, b, K, \{m\}$)
integrate $(2i\pi)^{-1} f$ on circle $ z-a = R$	intcirc($x = a, R, f, \{T\}$)
Other integration methods	
n -point Gauss-Legendre	intnumgauss($x = a, b, f, \{n\}$)
weights for n -point Gauss-Legendre	intnumgaussinit($\{n\}$)
quasi-periodic function, period $2H$	intnumosc($x = a, f, H$)
Romberg (low accuracy)	intnumromb($x = a, b, f, \{flag\}$)
Numerical summation	
sum of series $f(n), n \geq a$ (low accuracy)	suminf($n = a, expr$)
sum of alternating/positive series	sumalt, sumpos
sum of series using Euler-Maclaurin	sumnum($n = a, f, \{T\}$)
... Sidi summation	sumnumsidi($n = a, f$)
$\sum_{n \geq a} F(n)$, F rational function	sumnumrat(F, a)
$\dots \sum_{p \geq a} F(p^s)$	sumeulerrat($F, \{s=1\}, \{a=2\}$)
weights for sumnum, a as in DE	sumnuminit($\{\infty, a\}$)
sum of series by Monien summation	sumnummonien($n = a, f, \{T\}$)
weights for sumnummonien	sumnummonieninit($\{\infty, a\}$)
sum of series using Abel-Plana	sumnumap($n = a, f, \{T\}$)
weights for sumnumap, a as in DE	sumnumapinit($\{\infty, a\}$)
sum of series using Lagrange	sumnumlagrange($n = a, f, \{T\}$)
weights for sumnumlagrange	sumnumlagrangeinit
Products	
product $a \leq X \leq b$, initialized at x	prod($X = a, b, expr, \{x\}$)
product over primes $a \leq X \leq b$	prodeuler($X = a, b, expr$)
infinite product $a \leq X \leq \infty$	prodinf($X = a, expr$)
$\prod_{n \geq a} F(n)$, F rational function	prodnumrat(F, a)
$\prod_{p \geq a} F(p^s)$	prodeulerrat($F, \{s=1\}, \{a=2\}$)

Other numerical methods

real root of f in $[a, b]$; bracketed root	<code>solve($X = a, b, f$)</code>
...interval splitting, step s	<code>solvestep($X = a, b, s, f, \{flag = 0\}$)</code>
limit of $f(t)$, $t \rightarrow \infty$	<code>limitnum($f, \{\alpha\}$)</code>
asymptotic expansion of f (rational)	<code>asypnum($f, \{\alpha\}$)</code>
... $N + 1$ terms as floats	<code>asypnumraw($f, N, \{\alpha\}$)</code>
numerical derivation w.r.t x : $f'(a)$	<code>derivnum($x = a, f$)</code>
evaluate continued fraction F at t	<code>contfraceval($F, t, \{L\}$)</code>
power series to cont. fraction (L terms)	<code>contfracinit($S, \{L\}$)</code>
Padé approximant (deg. denom. $\leq B$)	<code>bestapprPade($S, \{B\}$)</code>

Elementary Arithmetic Functions

vector of binary digits of $ x $	<code>binary(x)</code>
bit number n of integer x	<code>bittest(x, n)</code>
Hamming weight of integer x	<code>hammingweight(x)</code>
digits of integer x in base B	<code>digits($x, \{B = 10\}$)</code>
sum of digits of integer x in base B	<code>sumdigits($x, \{B = 10\}$)</code>
integer from digits	<code>fromdigits($v, \{B = 10\}$)</code>
ceiling/floor/fractional part	<code>ceil, floor, frac</code>
round x to nearest integer	<code>round($x, \{\&e\}$)</code>
truncate x	<code>truncate($x, \{\&e\}$)</code>
gcd/LCM of x and y	<code>gcd(x, y), lcm(x, y)</code>
gcd of entries of a vector/matrix	<code>content(x)</code>

Primes and Factorization

extra prime table	<code>addprimes()</code>
add primes in v to prime table	<code>addprimes(v)</code>
remove primes from prime table	<code>removeprimes(v)</code>
Chebyshev $\pi(x)$, n -th prime p_n	<code>primepi(x), prime(n)</code>
vector of first n primes	<code>primes(n)</code>
smallest prime $\geq x$	<code>nextprime(x)</code>
largest prime $\leq x$	<code>precprime(x)</code>
factorization of x	<code>factor($x, \{lim\}$)</code>
...selecting specific algorithms	<code>factorint($x, \{flag = 0\}$)</code>
$n = df^2$, d squarefree/fundamental	<code>core($n, \{fl\}$), coredisc</code>
certificate for (prime) N	<code>primecert(N)</code>
verifies a certificate c	<code>primecertisvalid(c)</code>
convert certificate to Magma/PRIMO	<code>primecertexport</code>
recover x from its factorization	<code>factorback($f, \{e\}$)</code>
$x \in \mathbf{Z}$, $ x \leq X$, $\gcd(N, P(x)) \geq N$	<code>zncoppersmith($P, N, X, \{B\}$)</code>
divisors of N in residue class r mod s	<code>divisorslensstra(N, r, s)</code>

Divisors and multiplicative functions

number of prime divisors $\omega(n)$ / $\Omega(n)$	<code>omega(n), bigomega</code>
divisors of n / number of divisors $\tau(n)$	<code>divisors(n), numdiv</code>
sum of (k -th powers of) divisors of n	<code>sigma($n, \{k\}$)</code>
Möbius μ -function	<code>moebius(x)</code>
Ramanujan's τ -function	<code>ramanujantau(x)</code>

Combinatorics

factorial of x	<code>x!</code> or <code>factorial(x)</code>
binomial coefficient $\binom{x}{k}$	<code>binomial($x, \{k\}$)</code>
Bernoulli number B_n as real/rational	<code>bernreal(n), bernfrac</code>
$[B_0, B_2, \dots B_{2k}]$	<code>bernvec(k)</code>
Bernoulli polynomial $B_n(x)$	<code>bernpol($n, \{x\}$)</code>
Euler numbers	<code>eulerfrac, eulerreal, eulervec</code>
Euler polynomial $E_n(x)$	<code>eulerpol($n, \{x\}$)</code>
Eulerian polynomial $A_n(x)$	<code>eulerianpol</code>
Fibonacci number F_n	<code>fibonacci(n)</code>
Harmonic number $H_{n,r} = 1^{-r} + \dots + n^{-r}$	<code>harmonic(n, r)</code>
Stirling numbers $s(n, k)$ and $S(n, k)$	<code>stirling($n, k, \{flag\}$)</code>

Pari-GP reference card

(PARI-GP version 2.17.2)

number of partitions of n	<code>numbpart(n)</code>
k -th permutation on n letters	<code>numtoperm(n, k)</code>
...index k of permutation v	<code>permtotnum(v)</code>
order of permutation p	<code>permorder(p)</code>
signature of permutation p	<code>permsign(p)</code>
cyclic decomposition of permutation p	<code>permcycles(p)</code>

Multiplicative groups $(\mathbf{Z}/N\mathbf{Z})^*$, \mathbf{F}_q^*

Euler ϕ -function	<code>eulerphi(x)</code>
multiplicative order of x (divides ϕ)	<code>znorder($x, \{o\}$), fforder</code>
primitive root mod q / x .mod	<code>znprimroot(q), ffpriroot(x)</code>
structure of $(\mathbf{Z}/n\mathbf{Z})^*$	<code>znstar(n)</code>
discrete logarithm of x in base g	<code>znlog($x, g, \{o\}$), ffflog</code>
Kronecker-Legendre symbol $(\frac{x}{y})$	<code>kronecker(x, y)</code>
quadratic Hilbert symbol (at p)	<code>hilbert($x, y, \{p\}$)</code>

Euclidean algorithm, continued fractions

CRT: solve $z \equiv x$ and $z \equiv y$	<code>chinese(x, y)</code>
minimal u, v so $xu + yv = \gcd(x, y)$	<code>gcdext(x, y)</code>
half-gcd algorithm	<code>halfgcd(x, y)</code>
continued fraction of x	<code>contfrac($x, \{b\}, \{lmax\}$)</code>
last convergent of continued fraction x	<code>contfracpnqn(x)</code>
rational approximation to x (den. $\leq B$)	<code>bestappr($x, \{B\}$)</code>
recognize $x \in \mathbf{C}$ as polmod mod $T \in \mathbf{Z}[X]$	<code>bestapprnf(x, T)</code>

Miscellaneous

integer square / n -th root of x	<code>sqrtnint(x, n)</code>
largest integer e s.t. $b^e \leq x$, $e = \lfloor \log_b(x) \rfloor$	<code>logint($x, b, \{\&z\}$)</code>

Characters

Let $\chi = [d_1, \dots, d_k]$ represent an abelian group $G = \oplus (\mathbf{Z}/d_j\mathbf{Z}) \cdot g_j$ or any structure G affording a `.cyc` method; e.g. `znstar($q, 1$)` for Dirichlet characters. A character χ is coded by $[c_1, \dots, c_k]$ such that $\chi(g_j) = e(n_j/d_j)$.
 $\chi \cdot \psi$; χ^{-1} ; $\chi \cdot \psi^{-1}$; χ^k `charmul, charconj, chardiv, charpow`
order of χ `charorder(cyc, χ)`
kernel of χ `charker(cyc, χ)`
 $\chi(x)$, G a GP group structure `chareval($G, \chi, x, \{z\}$)`
Galois orbits of characters `chargalois(G)`

Dirichlet Characters

initialize $G = (\mathbf{Z}/q\mathbf{Z})^*$	<code>G = znstar($q, 1$)</code>
convert datum D to $[G, \chi]$	<code>znchar(D)</code>
is χ odd?	<code>zncharisodd(G, χ)</code>
real $\chi \rightarrow$ Kronecker symbol (D/\cdot)	<code>znchartokronecker(G, χ)</code>
conductor of χ	<code>zncharconductor(G, χ)</code>
$[G_0, \chi_0]$ primitive attached to χ	<code>znchartoprimitive(G, χ)</code>
induce $\chi \in \hat{G}$ to $\mathbf{Z}/N\mathbf{Z}$	<code>zncharinduce(G, χ, N)</code>
χp	<code>znchardecompose(G, χ, p)</code>
$\prod_p (Q, N) \chi p$	<code>znchardecompose(G, χ, Q)</code>
complex Gauss sum $G_a(\chi)$	<code>znchargauss(G, χ)</code>

Conrey labelling

Conrey label $m \in (\mathbf{Z}/q\mathbf{Z})^* \rightarrow$ character	<code>znconreychar(G, m)</code>
character \rightarrow Conrey label	<code>znconreyexp(G, χ)</code>
log on Conrey generators	<code>znconreylog(G, m)</code>
conductor of χ (χ_0 primitive)	<code>znconreyconductor($G, \chi, \{\chi_0\}$)</code>

True-False Tests

is x the disc. of a quadratic field?	<code>isfundamental(x)</code>
is x a prime?	<code>isprime(x)</code>
is x a strong pseudo-prime?	<code>ispseudoprime(x)</code>
is x square-free?	<code>issquarefree(x)</code>
is x a square?	<code>issquare($x, \{\&n\}$)</code>
is x a perfect power?	<code>ispower($x, \{k\}, \{\&n\}$)</code>
is x a perfect power of a prime? ($x = p^n$)	<code>isprimepower($x, \&n$)</code>
... of a pseudoprime?	<code>ispseudoprimepower($x, \&n$)</code>
is x powerful?	<code>ispowerful(x)</code>
is x a totient? ($x = \varphi(n)$)	<code>istotient($x, \{\&n\}$)</code>
is x a polygonal number? ($x = P(s, n)$)	<code>ispolygonal($x, s, \{\&n\}$)</code>
is pol irreducible?	<code>polisirreducible(pol)</code>

Graphic Functions

crude graph of $expr$ between a and b	<code>plot($X = a, b, expr$)</code>
High-resolution plot (immediate plot)	
plot $expr$ between a and b	<code>ploth($X = a, b, expr, \{flag\}, \{n\}$)</code>
plot points given by lists lx, ly	<code>plothraw($lx, ly, \{flag\}$)</code>
terminal dimensions	<code>plotsizes()</code>
Rectwindow functions	
init window w , with size x, y	<code>plotinit(w, x, y)</code>
erase window w	<code>plotkill(w)</code>
copy w to w_2 with offset (dx, dy)	<code>plotcopy(w, w_2, dx, dy)</code>
scale contents of w	<code>plotclip(w)</code>
scale coordinates in w	<code>plotscale(w, x_1, x_2, y_1, y_2)</code>
ploth in w	<code>plotrecth($w, X = a, b, expr, \{flag\}, \{n\}$)</code>
plothraw in w	<code>plotrecthraw($w, data, \{flag\}$)</code>
draw window w_1 at $(x_1, y_1), \dots$	<code>plotdraw($[[w_1, x_1, y_1], \dots]$)</code>

Low-level Rectwindow Functions

set current drawing color in w to c	<code>plotcolor(w, c)</code>
current position of cursor in w	<code>plotcursor(w)</code>
write s at cursor's position	<code>plotstring(w, s)</code>
move cursor to (x, y)	<code>plotmove(w, x, y)</code>
move cursor to $(x + dx, y + dy)$	<code>plotrmove(w, dx, dy)</code>
draw a box to (x_2, y_2)	<code>plotbox(w, x_2, y_2)</code>
draw a box to $(x + dx, y + dy)$	<code>plotrbox(w, dx, dy)</code>
draw polygon	<code>plotlines($w, lx, ly, \{flag\}$)</code>
draw points	<code>plotpoints(w, lx, ly)</code>
draw ellipse	<code>plotarc($w, lx, ly, \{flag\}$)</code>
draw line to $(x + dx, y + dy)$	<code>plotrline(w, dx, dy)</code>
draw point $(x + dx, y + dy)$	<code>plotrpoint(w, dx, dy)</code>

Convert to Postscript or Scalable Vector Graphics

The format f is either "ps" or "svg".	
as ploth	<code>plotlexport($f, X = a, b, expr, \{flag\}, \{n\}$)</code>
as plothraw	<code>plotlrawexport($f, lx, ly, \{flag\}$)</code>
as plotdraw	<code>plotexport($f, [[w_1, x_1, y_1], \dots]$)</code>