

exercisebank - manual

v0.1.4

(build 74)

Andreas Strauman

April 28, 2018

If you found any bugs or want new functionality, to contribute, view the commented source, get latest version of this package or get in touch with me, you can do all of that at <https://github.com/Strauman/exercisebank/>. If you have questions of functionality, kindly direct them to the community

<http://tex.stackexchange.com>. The author is active on this site regularly.

Contents

1	Motivation	3
2	Flow/Moderate start	3
2.1	Select	4
2.2	Exclude	4
2.3	Displaying numbers	5
2.4	Multiple	5
2.5	Mixnmatch	5
2.6	Solutions	5
2.7	Using <code>\At</code>	6
2.7.1	Making your own front page for a set	6
2.7.2	Printing the file name beneath the problem header	6
2.8	Dynamic figure path	6
3	Reference	7
3.1	Environments	7
	<code>intro</code> ^{→P. 7}	7
	<code>problem</code> ^{→P. 7}	7
	<code>solution</code> ^{→P. 7}	7
	<code>\DisplaySolutions</code> ^{→P. 7}	7
3.2	Making sets	8
	<code>\spritesets</code> ^{→P. 8}	8
	<code>\makeset</code> ^{→P. 8}	8
	<code>\about</code> ^{→P. 8}	8
	<code>\sprite</code> ^{→P. 8}	8
	<code>\exclude</code> ^{→P. 8}	8
	<code>\select</code> ^{→P. 8}	8

	<code>\DeclareExerciseCommand</code> ^{→ P. 8}	8
	<code>\exec</code> ^{→ P. 9}	9
	<code>\setName</code> ^{→ P. 9}	9
	<code>\pplabel</code> ^{→ P. 9}	9
	<code>\ppref</code> ^{→ P. 9}	9
	<code>\pref</code> ^{→ P. 9}	9
3.3	Configuration and options	10
	<code>\ShowNumbers</code> ^{→ P. 10}	10
	<code>\exercisebanksetup</code> ^{→ P. 10}	10
3.4	Internationalization	11
	<code>\translateExBank</code> ^{→ P. 11}	11
3.5	Triggers	11
	<code>\Trigger</code> ^{→ P. 11}	11
3.6	General reference	12
	<code>\ownLineNoSpacesGotIt</code> ^{→ P. 12}	12
	<code>\setExercisesDir</code> ^{→ P. 12}	12
	<code>\isin</code> ^{→ P. 12}	12
	<code>\exerciseFile</code> ^{→ P. 12}	12
3.7	Counters	12
3.8	Macro definitions	13
4	Changelog	13

1 Motivation

Exercises are saved as separate files containing part problems. These files can be used to make sets, and you can cherry-pick or exclude certain part problems as you see fit. This makes it easier to maintain and keep your exercises flexible as the syllabus changes.

2 Flow/Moderate start

I suspect that working with this package will break your current flow. So let's go through it. Most likely you would want to put all your exercises in a folder. To set the default folder, use `\exercisebanksetup`^{P.10}. In these examples we use `exercises/`.

exercises/myexercise.tex

```
\begin{intro}
  This introduces our problem
\end{intro}
\begin{problem}
  This is a partproblem 1,
  and will be hidden (just wait, you'll see)
\end{problem}
\begin{problem}
  This is a partproblem 2.
  This will not be hidden, but become part problem a!
\end{problem}
```

Let's build all of them first. In the main file, (the one where you include this package):

main.tex

```
\documentclass{article}
\usepackage{exercisebank}
\exercisebanksetup{exercise directory=exercises}
\makeset{myExerciseSet}{myexercise}
\begin{document}
  \buildset{myExerciseSet}
\end{document}
```

This builds the entire set, and adds Problem header and partproblem counters ((1a) and (1b)) by default.

2.1 Select

Now, let's build only the second problem.

```
main.tex

\documentclass{article}
\usepackage{exercisebank}
\exercisebanksetup{exercise directory=exercises}
\makeset{myExerciseSet}{\select{myexercise}{2}}
\begin{document}
  \buildset{myExerciseSet}
\end{document}
```

This should only build the intro and the one exercise you `\select`ed!

Now, say you want to hide the intro. Well all you have to do in this case is make the package treat the intro as a problem in regards to what is `\select`ed. Just add the optional argument `[intro]` to `\make`. That is switch

```
\makeset{myExerciseSet}{\select{myexercise}{2}}
```

with

```
\makeset[intro]{myExerciseSet}{\select{myexercise}{3}}
```

Notice that there are 3 ‘partproblems’ now since we have to count the intro!

2.2 Exclude

But what if you have an exercise with 12 partproblems, and you only want to exclude the 7th partproblem? Well, then `\Exclude` is here to rescue the day for you.

```
\makeset{myExerciseSet}{\exclude{soManyExercises}{7}}
```

Here it's important to note that the `[intro]` argument would not make the intros disappear. If we wanted to only exclude the intro from our previous example file `exercises/myexercise.tex` we would do

```
\makeset[intro]{myExerciseSet}{\exclude{myexercise}{1}}
```

So we're excluding the partproblem 1. But that's the intro when we send the `[intro]` optional argument

2.3 Displaying numbers

If you have many part problems, counting the problem numbers can be a real hassle. Just use `\ShowNumbers`, and a big number will appear in front of every part problem!

2.4 Multiple

In `\makeset` you can just separate exercises with commas! Here is an example:
Let's say you have two files with exercises. One located in `exercises/circuits/RLC.tex` and one in `exercises/ohm/ohmsGeneralLaw.tex`, and you want to include partproblem 1 through 5 from `RLC.tex` and all of the exercises from `ohmsGeneralLaw.tex`.

```
\makeset{\select{circuits/RLC}{1,...,5}, ohmsGeneralLaw}
```

This will divide it up with problem headers. So that what is in the `RLC.tex`-file will be Problem 1, and `ohmsGeneralLaw.tex` Problem 2.

2.5 Mixnmatch

What if you want to make both of them the same exercise? Well, then you pass the `[nohead]` argument to `\makeset`:

```
\makeset[nohead]{\phead, \select{circuits/RLC}{1,...,5}, ohmsGeneralLaw}
```

The `\phead` command makes a problem header. You can pass them as much as you want:

```
\makeset[nohead]{\phead, \select{circuits/RLC}{1,...,5},  
ohmsGeneralLaw, \phead, someOtherExercise, moreExercises}
```

2.6 Solutions

The last thing to cover then is solutions. In your exercise files you just use the solution environment

```
\begin{solution}  
Solution goes here  
\end{solution}
```

They are hidden by default, so you would have to use `\DisplaySolutions` in your main file to display them.

2.7 Using `\At`

2.7.1 Making your own front page for a set

To create your own front page for each set, you'd use `\At\StartBuildset{\FrontPageContents}`. Anything you send in to `\At\StartBuildset` will be executed before the first problem starts:

```
\At\StartBuildset{
  \input{myFrontpage}
}
```

2.7.2 Printing the file name beneath the problem header

Maybe you want to see what files are what problems. One way to do that is hook into the `\At\VeryBeginProblem` and use `\exerciseFile`^{→P.12}. This is the command that the headers call, so anything you put in there will be executed right after the headers.

```
\At\VeryBeginProblem{
  \exerciseFile\
}
```

Note that the `\AtBeginProblem` is executed *before* the headers.

2.8 Dynamic figure path

Exercisebank automatically allows you to `\input` and `\includegraphics` from the same as exercise is in. E.g. if you have a declared the option

```
\exercisebanksetup{exercise directory=exercises}
```

and you have a file `exercises/somedir/myexercise.tex`, you can put a figure in `exercises/somedir/` or make a directory with the same name as the file `exercises/somedir/myexercise/`. Then if you put a figure `exercises/somedir/myfig.png` or `exercises/somedir/myexercise/myfig.png` you can just do

```
\includegraphics{myfig}
```

You can change the root dir by doing `\exercisebanksetup{figure root directory→P.10=figures}`. See the `figure root directory→P.10` key for more info.

That covers the basics. Enjoy

! `\begin{problem}, \end{problem},`
`\begin{solution}, \end{solution},`
`\begin{intro}` and `\end{intro}` has to be on their own line without any spaces!

3 Reference

3.1 Environments

`\DisplaySolutions`

Turns on the solutions, so they are shown.

```
\begin{problem}  
  <environment content>  
\end{problem}
```

Inside the `\keyRef{exercise directory}`, you keep your exercises. Inside the exercise file you'd use a problem environment to write your partproblems. It might be a little confusing that you're using `\begin{problem}` instead of `\begin{partproblem}` when you're writing a partproblem, but it's less typing.

```
\begin{solution}  
  <environment content>  
\end{solution}
```

Things inside here is only visible if `\DisplaySolutions` are given before `\begin{document}`

! `\end{solution}` has to be on it's own line without any leading spaces!

```
\begin{intro}  
  <environment content>  
\end{intro}
```

Sometimes you'd want to introcude your exercises and tell a little bit about it. Maybe have a figure there also. Those things should go inside this environment. This can be treated as a problem in terms of counting. See `\makeset`^{→P.8} for more info.

3.2 Making sets

`\spritesets{⟨setlist⟩}`

This is a command that is used by `sprite` to determine what sets are shown in `sprite`. If this is not given, `sprite` uses all sets given in `\makset`

`\makeset[⟨intro,nohead⟩]{⟨filable⟩}`

This command is the one you use to make a set! Later you use `\buildset` to build the sets you make. The `⟨filable⟩` argument is either the name of the file relative to the `\setExercisesDir`-path (default is nothing, so it's in the root path), or you could use the `\select` or `\exclude` to respectively cherry pick or exclude exercises. (See their docs).

`[⟨intro⟩]` this counts the intro environment as a part problem, so that you can `\select` or `\exclude` the intro

`[⟨nohead⟩]` prevents the builder from adding a problem header. This is handy if you want to create an exercise that is composed of multiple parts. You can use the `\phead` to insert the problem header where you want it

```
\makeset[nohead]\{\phead, \select{myexercise}{1,2,3}}
```

`\about{⟨text⟩}`

This contains information about an exercise set. It is intended to be on the top of an exercise, explaining short what the exercise is about. It's only visible when using `\sprite`

`\sprite[⟨PiP⟩]`

This is a way to visualize all exercises. It takes one optional argument which is how many pages inside one page. Defaults to 4

! If `\sprite` is used, it should be the only command in `\begin{document}\end{document}`

`\exclude{⟨exerciseFileName⟩}{⟨Comma separated numbers⟩}`

As you can see in the intro section of the documentation, this is for excluding partproblems To be used in `\makset`

`\select{⟨exerciseFileName⟩}{⟨Comma separated numbers⟩}`

As you can see in the intro section of the documentation, this is for cherry picking partproblems To be used in `\makset`

`\DeclareExerciseCommand{⟨command⟩}{⟨actions⟩}`

This can be used later in makesets. E.g. `\DeclareExerciseCommand{\pbreak}{\clearpage}` will make `\pbreak` behave like `\clearpage` in the set:

```
\makeset[nohead]{%
  \phead,
  myExercise,
  \pbreak,
  myExerciseOnNewPage%
}
```


`\exec{<macros>}`

You can use this in `\makeset` to execute commands between problems. E.g. to insert a new page in between two problems when using nohead:

```
\makeset[nohead]{2}{\phead,my/exercise,\exec{\clearpage},next/exercise}
```

`\setName`

This variable prints out the name of your set that you sent to `\buildset`. The following example prints "Exercise set number 1" and "Exercise set number 2" on the top of each set

```
\At\StartBuildset{
  Exercise set number \setName
}
%... \makesets here ...%
\begin{document}
  \buildset{1}{myexercise}
  \buildset{2}{myexercise}
\end{document}
```

`\pplabel{<label>}`

Labels a partproblem. You can reference to it later using `\ppref{<label>}`

`\ppref{<label>}`

Reference a partproblem created by `\pplabel{<label>}`. This prints e.g. 1c)

`\pref{<label>}`

Reference a partproblem created by `\pplabel{<label>}`. This prints e.g. 1

3.3 Configuration and options

You can do a lot of configurations on this package, and probably even more to come in later versions!

`\ShowNumbers`

Shows the numbers in front of the part problems and intros that should be used with `\exclude` and `\select`

Uv0.1.4
2018/04/28

`\exercisebanksetup{[/key/values]}`

Here is a list of the different keys and their meaning

Nv0.1.0
2018/04/08

`part problems`= $\langle On/Off \rangle$ ($\langle default \rangle$ =On)

This is whether or not to do part problems. E.g. 1a), 1b) etc. If this is turned Off, then the part problems will be treated as problems

`tighten paragraphs`= $\langle True/False \rangle$ ($\langle default \rangle$ =True)

Disabling this will prevent the package from attempting to prevent part problems to scatter across pages

`problem header`= $\langle macro \rangle$ ($\langle default \rangle$ =see below)

This sets the problem header. To access the translation of the problem text, use `\@tr{Problem}`, and the problem counter is accessed with `\theproblemcounter`.

Defaults to

`\normalfont\Large\bfseries\@tr{Problem} \theproblemcounter`.

`part problem header`= $\langle macro \rangle$ ($\langle default \rangle$ =see below)

This sets the problem header. To access the current problem, use `\theproblemcounter`, and then the current part problem `\thepartproblemcounter`. To make it a letter, as per default use `\alph{partproblemcounter}`

Default is:

`\large\textbf{(\theproblemcounter\alphpartproblemcounter)}`

`solution header`= $\langle string \rangle$ ($\langle default \rangle$ =see below)

`\large{\textbf{\@trSolution}}`:

`exercise directory`= $\langle dir \rangle$ ($\langle default \rangle$ =./)

This key is used for setting the default exercise directory.

`figure root directory`= $\langle dir \rangle$ ($\langle default \rangle$ = $\langle exercise directory \rangle$)

Exercisebank automatically allows you to `\input` and `\includegraphics` from the same folder that your exercise is in, as well as a folder with the same name as the exercise file. This is elaborated in the intro section. However, you might want to put the figures inside a different directory. For example if you have one directory containing your problems called `exercises/`, set with `exercise directory`, and a file containing the exercise: `exercises/faradaysLaw/ACGenerate.tex`. Then by default figures in the directories `exercises/faradaysLaw/` and `exercises/faradaysLaw/ACGenerate/` can be included by just doing `\includegraphics`. And if you want to change the root of this directory to be `figures`, such that exercisebank looks for figures in `figures/faradaysLaw/` and `figures/faradaysLaw/ACGenerate/` You would use this option in the setup: `\exercisebanksetup{figure root directory=figures}`

```
\exercisebanksetup{exercise directory=exercises,part problems=Off,solution 2
  \header={\textbf{SOL:}}}
```

3.4 Internationalization

`\translateExBank`{*<Translation key/vals>*}

This is to translate the text inside the package. As of now the available key/values are

- Problem
- Solution

The Norwegian translation would then be done with

```
\translateExBank{Problem=Oppgave, Solution=Løsning}
```

3.5 Triggers

`\Trigger`{*<Any Macro>*}

See `\At` → P. 12

Available triggers:

`\Trigger\BeginPartproblem:`

Triggers before a partproblem is inserted

`\Trigger\VeryBeginPartproblem:`

Triggers right after `\BeginPartproblem`. This is so that the user can do stuff before the actual headers start. The partproblem headers are invoked by `\At\VeryBeginPartproblem`

`\Trigger\InputExercise:`

Triggers before a file is included

`\Trigger\BeginProblem:`

Triggers before a file is included, but only if problem headers are to be written (no [nohead] given)

`\Trigger\EndProblem:`

Triggers right after problem is included if [nohead] *not* given

`\Trigger\BeginBuildset:`

Triggers right before a set has begun building (not if `\sprite` is used). You might want to put your set-header here

`\Trigger\EndBuildset:`

Triggers when a set has stopped building (not if `\sprite` is used)

3.6 General reference

`\ownLineNoSpacesGotIt`

This is to annoy the user enough to get his attention about the requirements of the `problem`^{→P.7}, `solution`^{→P.7} and `intro`^{→P.7} environments.

! DEPRECATED! use `\exercisebanksetup`^{→P.10} with `exercise directory`^{→P.10} instead!

`\setExercisesDir{<directory>}`

! `\setExercisesDir` is deprecated! use `\exercisebanksetup`^{→P.10} with `exercise directory`^{→P.10} instead!

This is the directory, relative to the file you included the package, where the package should be looking for exercises. Default is the same directory as your main file (the one you build).

`\isin{<haystack>}{<needle>}{<True>}{<False>}`

`<haystack>` is a comma separated list of integers

`<needle>` is an integer

Executes `<True>` if `<needle>` is found in `<haystack>` else executes `<False>`

This package also includes some extra stuff. For example the `\At` and `\Trigger`

`\At{<AnyMacro>}`

Here you can send any macro because it isn't evaluated! For example `\At\BeginSomething` is fine and even if `\BeginSomething` is not defined. Also and when using `\Trigger` it just ignores it if it didn't exist. It's pretty similar in function as to `\AtBeginDocument`.

```
\At\BeginSomething{DoSomething}
Which is triggered with
\Trigger\BeginSomething, this evaluates to DoSomething
```

`\exerciseFile`

This is a 'read-only' macro that contains the name of the current exerciseFile

3.7 Counters

`problemcounter`-counter holds the current problem number and `partproblemcounter`-counter holds the current partproblem *number*.

3.8 Macro definitions

`\At`^{→ P. 12}
`\DeclareExerciseCommand`^{→ P. 8}
`\DisplaySolutions`^{→ P. 7}
`\ShowNumbers`^{→ P. 10}
`\Trigger`^{→ P. 11}
`\about`^{→ P. 8}
`\exclude`^{→ P. 8}
`\exec`^{→ P. 9}
`\exerciseFile`^{→ P. 12}
`\exercisebanksetup`^{→ P. 10}
`\isin`^{→ P. 12}
`\makeset`^{→ P. 8}
`\ownLineNoSpacesGotIt`^{→ P. 12}
`\pplabel`^{→ P. 9}
`\ppref`^{→ P. 9}
`\pref`^{→ P. 9}
`\select`^{→ P. 8}
`\setExercisesDir`^{→ P. 12}
`\setName`^{→ P. 9}
`\sprite`^{→ P. 8}
`\spritesets`^{→ P. 8}
`\translateExBank`^{→ P. 11}

4 Changelog

v0.0.2b11 2018/04/02

- Updated documentation syntax.

v0.0.3b38 2018/04/03

- Updated triggers doc
- added trigger `\VeryBeginPartproblem`

v0.0.3b40 2018/04/03

- Added examples that uses the `\At`^{→ P. 12} command.
- Making front page and other snacks

v0.0.4b44 2018/04/03

- Changed design of part problems. (Looks much better now!)

v0.0.5b46 2018/04/03

- Fixed partproblems and solutions to fit on pages using `\filbreak`.

v0.1.0 2018/04/08

- Fixed title of documentation to match actual package.
- Fixed weird paragraph styling when displaying solutions
- Added a few package options. More to come!

v0.1.1 2018/04/13

- Added `\exec→P.9`, which allows the user to execute macros between problems
- Bug fix: `\At→P.12` would cause crash due to latexmk multiple builds
- Bug fix: `\sprite→P.8` wouldn't build correctly
- Bug fix: misc bugs involving `\makeset→P.8`, `??→P.??`, `nohead` and `??→P.??`

v0.1.2 2018/04/17

- Fixed bug that `\select→P.8` and `\exclude→P.8` not working as expected.
- Added `\ShowNumbers→P.10` for displaying numbers related to use in `\select→P.8` and `\exclude→P.8`

v0.1.3 2018/04/20

- Added custom dynamic figure path `figure root directory→P.10`.
- Fixed bugs related to `??→P.??` and the commands used in `\makeset→P.8`-lists.

2018/04/28

- Fixed paragraph tightening when displaying solutions
- Introduced `\DeclareExerciseCommand→P.8`
- Fixed bug with `\exec→P.9`
- Iteration over items now uses a more lightweight approach.
For commands that takes 'lists' as arguments (`\makeset→P.8`, `\select→P.8` and `\exclude→P.8`), the last item of the list can be terminated with new line or spaces without problems.
For commands that takes 'lists' as arguments, the entries in the list are now trimmed whitespaces on both sides.

- Fixed bug where `\ppref→P.9` did not reference letter in part problem.